

# SOLVALL

# REMOVABLE SOLVENT CLEANER FOR STONE MATERIALS



# User guide

#### **DESCRIPTION:**

Thickened mixture of solvents, non-ionic surfactants, emulsifiers.

#### FIELDS OF APPLICATION:

To carry out a deep and film-stripping cleaning of stone materials such as terracotta, stone, marble, granite, cement agglomerates.

# **CHARACTERISTICS:**

SOLVALL is a solvent cleaner for stone materials such as cotto, stone, glazed ceramic, klinker, porcelain tiles, cement, terrazzo, etc.

#### SOLVALL:

- removes resins and paints from absorbent stone materials;
- compared to conventional paint strippers has lower evaporation speed, longer application time and a deeper removing action;
- it is easily emulsifiable when rinsing with water and can be removed with liquid vacuums;
- does not leave unpleasant odors.

# **INSTRUCTIONS FOR USE:**

- Spread SOLVALL on the surface and let it work 15 30 minutes up to a maximum of 8-12 hours in the
  most extreme situations;
- Then wipe the wet surface of SOLVALL with buffers, black discs or with tynex brushes;
- Emulsify with water and remove the residue;
- For the deepest removal of resinous-oily treatments, it is recommended after washing with SOLVALL to perform a strong cleaning with the SGRISER product;
- On acid-resistant materials, such as terracotta, granite or unpolished stones, it is recommended to make the first rinse with DELICACID for a deeper cleaning of the porosity of the material;
- Finally, complete the rinse cycle with water;
- · Repeat the application if necessary.

Do not apply SOLVALL on wood, synthetic agglomerate and painted metal surfaces.

#### PRECAUTIONS:

• protect all painted and plastic surfaces from contact with SOLVALL.

# NOTES:

Our indications are based on the current knowledge of the research and are intended to give the best guidance to the buyer-user. However, such indications require preliminary examination and testing of the fields of use, the types of materials present and the various conditions of application. The user decides independently on the suitability and the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev8-Ver28112023

#### WARNINGS:







Hazard statements: Flammable liquid and vapour. – May be fatal if swallowed and enters airways. – Causes serious eye irritation. – May cause an allergic skin reaction. – May cause drowsiness or dizziness.

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. – Do NOT induce vomiting. – Wear protective gloves/ protective clothing / eye protection / face protection. – Avoid breathing dust / fume / gas / mist / vapours / spray. – Call a POISON CENTRE / doctor / . . . if you feel unwell. – Store in a well-ventilated place. Keep container tightly closed. – Take off immediately all contaminated clothing and wash it before reuse.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatic, 1-methoxy-2-propanol; Benzyl alcohol.

UFI: 0A20-M04T-A00X-HCJE

Rev9-Ver12022025

#### **PACKAGING:**

- 1 lt conf. Can 6 pieces box;
- 5 lt conf. Watertight 4 pieces box.

### YIELD:

• 1lt / 4-15 m², depending on the dirt to be removed and the absorption of the material.

# **TECHNICAL DATA:**

- · Physical state: yellowish liquid
- Specific gravity (g/cm3) at 20 °C: 0,99
- pH: n.a.
- Flame point (ASTM): 40°C
- · Solubility in water: insoluble in water.

# STORAGE:

Keep the product tightly closed and at a temperature between 5 and 30 °C in an aerated environment, away from heat sources and not exposed to sunlight for a long time. When stored at low temperatures (<10 °C) the product can become dense, but without affecting its use or performance. The stored product has a useful life of 5 years.